

B6

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G07B		A2	(11) International Publication Number: WO 98/20461
			(43) International Publication Date: 14 May 1998 (14.05.98)
(21) International Application Number: PCT/US97/15856		(81) Designated States: CA, JP, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 7 November 1997 (07.11.97)		Published Without international search report and to be republished upon receipt of that report.	
(30) Priority Data: 60/030,537 7 November 1996 (07.11.96) US 60/050,043 18 June 1997 (18.06.97) US 60/054,105 29 July 1997 (29.07.97) US			
(71) Applicant (for all designated States except US): ASCOM HASLER MAILING SYSTEMS, INC. [US/US]; 19 Forest Parkway, Shelton, CT 06484 (US).			
(72) Inventors; and (75) Inventors/Applicants (for US only): SCHWARTZ, Robert [US/US]; 191 Linden Avenue, Branford, CT 06405 (US). BROOKNER, George [US/US]; 11 Surrey Drive, Norwalk, CT 06851 (US). NACLERIO, Edward [US/US]; 49 Scenic Road, Madison, CT 06443-1738 (US).			
(74) Agent: FERENC, Stanley, D., III; Oppedahl & Larson, Suite 309, 1992 Commerce Street, Yorktown Heights, NY 10598-4412 (US).			

BEST AVAILABLE COPY

(54) Title: SYSTEM FOR PROTECTING CRYPTOGRAPHIC PROCESSING AND MEMORY RESOURCES FOR POSTAL FRANKING MACHINES



(57) Abstract

An improved system for protecting cryptographic processing and memory for postal franking machines. Appropriate cryptographic processing and memory resources are contained in a Postal Security Device (PSD), which defines a cryptographic and physical boundary. Cryptographic processing occurs in the PSD, which provides security to these resources, thereby minimizing a successful fraudulent attack on the system. Speed of the cryptographic processing is also increased. The PSD may be in the form of an Applications Specific Integrated Circuit (ASIC) or Personal Computer Memory Card International Association (PCMCIA) Card.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

SYSTEM FOR PROTECTING CRYPTOGRAPHIC PROCESSING AND MEMORY
RESOURCES FOR POSTAL FRANKING MACHINES

RELATED APPLICATIONS

This application claims priority from pending U.S.
5 Provisional Application Serial Nos. 60/030,537,
60/050,043, and 60/054,105, filed on November 7, 1996,
June 18, 1997, and July 29, 1997, respectively, which are
hereby incorporated by reference.

TECHNICAL FIELD

10 This invention is directed to a system for
protecting cryptographic processing and memory resources
for postal franking machines.

BACKGROUND ART

15 In countries throughout the world, a postal
customer may obtain postage from the postal authority in
several ways, including the purchase of stamps and the
use of a postage meter. When a postage meter is used,
there is a security concern since the meter is dispensing
value, and without sufficient security, the value could
20 be stolen from a meter by unscrupulous parties. Concerns
include use of the meter to dispense postage for which
the Postal Authority has not been compensated and use of
the meter which was not authorized by the lawful operator
of the meter.

25 These security concerns have always been
present, even when a postage meter was essentially a
purely mechanical letterpress. As the postage meter
evolved through the 20th century to an electronic
configuration, letter-press printing was represented in a
30 rotary drum movement impressing an image onto a

mailpiece, as well as a flat-bed approach meshing a mailpiece on a platen assembly against a printing die to produce an image onto a mailpiece. The postage meter is now taking on a new role of digitally printing postage, thus no longer requiring letter-press printing.

When a postage meter utilizes letter-press printing, security concerns are typically addressed, in part, by the physical attributes of the meter. Not only do the attributes of the meter (case material, etc.) provide protection against the unauthorized use of the meter, the attributes also provide a means to detect whether an attempt has been made to make unauthorized use of the meter evidenced by visible deliberate damage to the meter's case. With evolution of the "meter," greater security against fraudulent attacks on the meter is needed. With the increase in the availability of elaborate technologies and sophisticated hacking capabilities, Postal Authorities around the world, including the United States Postal Service, are concerned with the ability to defraud the Postal Authorities by falsifying postal indicium, particularly when such indicium is digitally printed.

One approach which has been taken to increase the security of evolved meters is to employ cryptographics to the creation and application of the postal indicia. In order for this approach to be an effective security measure, however, there must be sufficient physical security for the cryptographic processing and memory to eliminate a successful fraudulent attack on the system. In order for this to be a commercially viable approach, cryptographic processing must be performed in a timely manner.

DISCLOSURE OF THE INVENTION

In accordance with the present invention, there is provided a greatly improved system for protecting cryptographic processing and memory, which also results in faster cryptographic processing. According to the invention, it is provided that the appropriate cryptographic processing and memory resources are contained in a Postal Security Device (PSD). The PSD provides physical security to these resources, thereby eliminating a successful fraudulent attack on the system. The PSD may be in the form of an Applications Specific Integrated Circuit (ASIC) and is preferably mounted on a portable device with an interface such as a Personal Computer Memory Card International Association (PCMCIA) Compliant Card or other form factor capable of supporting the integrity of the PSD.

BRIEF DESCRIPTION OF DRAWINGS

Fig. 1 is a block diagram showing the basic functional makeup of the PSD cryptographic processor in the present invention.

Fig. 2 is a block diagram of the PCMCIA Card PSD of the present invention.

Fig. 3 is a block diagram showing the PSD of the present invention operating in secure high speed instruction cache operation.

MODES FOR CARRYING OUT THE INVENTION

Referring to Fig. 1, an ASIC embodiment of a PSD is shown generally at 5 and includes zeroing circuitry 10, read-only-memory 12, random-access-memory 14, switching/control logic 16, a control cryptographic

processor 18, non-volatile memory 20, crypto key retention 22, signature algorithm execution 24, random number generator 26, real time clock 28, interrupt control and porting 30, clock circuit 36, secure hash acceleration circuit 44, secure memory management unit 54, and host interface 44 all within a cryptographic boundary 34. The Random Number Generator 26 within this block provides a source for non-predictable random numbers typically required in systems employing cryptographic technology. The clock circuit 28 is an on-chip realtime clock for secure time keeping. External to the ASIC PSD are a battery 32 for retaining memory contents in the absence of main power to the ASIC, and one or more crystals 37 which provide clock reference timing for the various subcircuits within the ASIC. Such a PSD contains working memory, storage memory, and firmware necessary to execute cryptographic algorithms, within its cryptographic boundary, including, but not limited to DES and RSA encryption, as well as digital signature creation and validation. Information that must be retained, as Master Key, Public Key, Private Key, and the like are secured within a non-volatile memory or battery backed up memory of the PSD. Although the battery and crystals are outside the cryptographic boundary of the ASIC in this embodiment, these components can be also integrated into the same package as the ASIC silicon die.

The ASIC provides physical security to the data stored thereon as the circuits are inaccessible without destroying circuit operation. The secure data stored on an ASIC includes data encryption keys which cannot be extracted or modified without destroying PSD operation. The encryption engine 24 includes the capability of receiving data, processing the received data by performing encryption or decryption operations.

The individual components of the ASIC may also be integrated within a PCMCIA Card, or preferably the custom integrated circuit (ASIC) is further integrated and embodied as a PCMCIA Card. The PCMCIA Card provides additional physical security through its housing for the processing unit for the storage and accounting of all funds, audit and secure support data required to produce and validate the addition and removal of postage value. As described above, one of the preferred embodiments encloses the ASIC or its components in a PCMCIA card. More generally, the invention contemplates enclosing the ASIC or its components in any package having a relatively small form factor. For example, any form factor that is more or less pocket-sized or that is more or less capable of being mailed in an envelope will be convenient. Such a package must necessarily have a communications port capable to interfacing with the postal franking device and a host, discussed below, preferably a parallel data and address bus such as is employed in a PCMCIA card. Alternatively the port could be a serial bus such as a high-speed universal serial bus. If the application does not require high speed, an infrared (LED-phototransistor) link may be used. Said secure processing unit contains working memory, storage memory, and firmware necessary to execute cryptographic algorithms, within a cryptographic boundary, including but not limited to DES and RSA, as well as digital signature creation and validation. Information which must be retained, such as Master Keys, Public Keys, Private Keys, and the like are secured within a non-volatile memory or battery backed up memory.

The security of the PSD implemented in a PCMCIA Card is a combination of data integrity, authentication, non-repudiation, and confidentiality. Data integrity is realized through the use of cryptographic checksums (one-way hashes) over the data. This function produces a

6

small value that uniquely represents the data, such that if any single bit is altered the hash value changes significantly. The digital signature is obtained by performing a cryptographic operation on the resultant hash of the data. Authentication is realized by the fact that the receiving party can verify the digital signature on a transmission and be assured the transmission was originated by a trusted source and not other fraudulent parties. Non-repudiation is achieved by the fact that the originator of the message cannot deny the message contents as it is possible to generate the verifiable digital signature only with the originator's unique private key. Confidentiality is the use of encryption to protect the data from unauthorized disclosure.

To ensure operational security, the PSD cannot operate as a standalone device and requires a host system to perform its functions. The PSD typically communicates directly with a host system to carry out its primary objective of indicia creation. Additionally, through the host system a user can access the PSD to review the ascending and descending register values, piece count, watchdog timeout date, and refill history logs; activate PSD diagnostics; and with proper supervisor authorization, set up and delete PINs for individual users. The PSD may also provide the user with certain operational error messages such as a low-postage warning and watchdog timeout condition through the host user interface. The host system may also maintain certain log files; these log files are required to be signed by the PSD with its private key. The host system will transfer the data to sign to the PSD and the PSD will return a digital signature and a certificate (which contains the public key which is unique to the PSD) that can be used later to verify the digital signature.

7

The PSD supports input and output functions with appropriate interfacing devices compatible with the PSD physical, link layer, and application protocols. Due to the secure nature of the PSD, the device does not provide user accessible diagnostic features. Rather, the PSD has an extensive built-in self test suite which is run upon power up. The tests preferably include the normal code memory verification tests, RAM tests, verification of accounting register and data log integrity, and execution of sample cryptographic calculations with known results to verify full functionality of the PSD. Upon successful completion of these tests, the PSD will be enabled to dispense postage funds. If any of the tests fail, the PSD will output its current ascending register and descending values. The host may also obtain the same information via a device audit request message. This will provide the host with additional information which may be forwarded to a Host infrastructure for the purposes of auditing the PSD. Upon the receipt and verification of a Host infrastructure-generated device audit message, preferably the PSD will reset its internal watchdog timer to accommodate control and transaction date information.

It is understood by one skilled in the art that the PSD of the present invention need not be physically located with the postal franking device; it only need be in communication with the postal franking device. For example, it may be located on the host or a computer network. In the instance of the PSD including a PCMCIA Card, the PSD may be connected to the franking device for operation and then disconnected and connected to the host for creation of the log files, etc., through a standard PCMCIA slot.

Referring now to Fig. 2, a block diagram of the embodiment of the PCMCIA Card PSD of the present invention interfacing with a host controller is shown, including host controller 64, timeout circuit 66, memory 5 arbiter 68, controller 70, and memory 72. It is envisioned that a number of forms of attack can be executed against the PCMCIA Card PSD wherein an attacker attempts to obtain additional data from the PSD, or otherwise compromise its integrity, by holding the bus 10 for an excessive period of time. Timeout circuit 66 operates to limit the amount of time host controller 64 may have to complete a bus transaction, and will terminate a host-initiated bus transaction if the transaction exceeds a predetermined time limit.

15 When host 64 wishes to access the PSD implemented in a PCMCIA Card, it waits until read signal 74 is asserted and then asserts select signal 76. This signal is input to timeout circuit 66, which initiates a predetermined timeout interval. Host controller 64 then 20 initiates a read or write cycle by asserting the appropriate read and write signals and setting up the address and data busses accordingly.

Timeout circuit 66 provides a separate select signal 78 to memory arbiter 68, which is effectively a 25 dual port memory controller containing logic which defines conditions under which controller 70 and host controller 64 have access to memory 72. When host controller 64 has access to memory 72, arbiter 68 asserts a hold signal 80 to controller 70, which tells controller 30 70 to temporarily hold off any further accesses of memory 72. Under these circumstances, controller 70 is typically idle unless it is performing an internal operation not requiring an external memory access.

Arbiter 68 allows read and write signals 82 and 84, as well as address and data busses 86 and 88, to pass onto memory 72. Following a successful bus transaction, host controller 64 deasserts select signal 74 to timeout
5 circuit 66 to indicate the normal end of the bus transfer. Timeout circuit 66 likewise deasserts select signal 78 to arbiter 68, which removes host controller's signal levels on the read, write, address and data busses (82, 84, and 86) to memory 72 and signals the controller
10 70 that it can access memory 72 by deasserting hold signal 80.

If host controller 64 takes too long to complete the bus access, timeout circuit 66 deasserts ready signal 74 to the host controller and select signal
15 78 to arbiter 68. This causes arbiter 68 to remove host controller's 64 read (84), write (82) address (88) and data (86) signals from memory 72. Hold signal 80 to controller 70 is released to controller 70 can again access memory 72. Alternatively, timeout circuit 66
20 could also signal controller 70 that the fault occurred by asserting interrupt signal 90 to that device. Logic in the controller 70's software could be invoked to categorize the problem as a random fault or an attempt to compromise the PSD. If controller 70 determines
25 tampering has been attempted, the controller would refuse further host controller 64 accesses and force the customer to report the situation to the manufacturer, for example, remotely through a telephone call or other network communication or by returning the device.

30 A preferred embodiment of the PSD implemented on a PCMCIA Card would restrict the area in memory 72 that host controller 64 can access. For example, access can be limited to no access, read-only, write-only, read-write, etc., and the address range in memory 72 can be

restricted to a subset available to controller 70. In this manner, controller 70 can hide certain information, such as its most critical security parameters, from both observation or overwriting.

5 Host interface 42 incorporates timeout circuit 66, PCMCIA memory arbiter 68, and PSD controller 70. Controller 70 corresponds to crypto processor 18 in figure 1. Timeout circuit 66 and arbiter 68 would thus preferably be incorporated into the PSD ASIC but may be
10 added as discrete circuits on the PCMCIA card.

 The PSD of the present invention may be used with existing public/private key cryptographic techniques known in the art. See, for example, U.S. Patent Nos. 5,237,506, 5,606,507 and 5,666,284, which are
15 hereby incorporated by reference. The speed with which such encryption is performed, however, may be increased by the use within the PSD of a Secure Memory Management Unit 96 (SMMU). Preferably, this is obtained from Atalla Corp., of San Jose, California, which is a Tandem
20 Company, and VLSI Technology, of San Jose, California.

 As shown in Fig. 3, Memory 98 external to the PSD contains encrypted code. SMMU 96 obtains the encrypted code 100 in portions to be processed by encryption engine 104, in such a manner that it acts as a
25 feed for encryption engine 104. The encryption engine 104 utilizes the appropriate decryption key provided to it by the SMMU 96. This decryption key is securely stored in the PSD ASIC and is never output and so is never known to a potential attacker. The decrypted
30 output from encryption engine 104 is then placed into RAM 106 (also 14 in Fig. 1). Fig. 3 shows the output of RAM 106 going to processor 108 (also 18 in Fig. 1). Thus, Fig. 3 depicts secure high speed instruction cache

operation. The overall benefit of the SMMU is realized by the fact that a would-be attacker cannot substitute software instructions into the code to alter the intended functionality and that could give the attacker access to
5 the master, private, or public keys held within the PSD ASIC.

While there have been described what are believed to be the preferred embodiments of the invention, those skilled in the art will recognize that
10 other and further modifications may be made thereto without departing from the invention and it is intended to claim all such changes and modifications as fully within the scope of the invention.

WE CLAIM:

1. A system for increasing the security and efficiency of cryptographic processing resources for postal franking machines, comprising:

- 5 (a) an encryption engine;
- (b) means for obtaining encrypted code in portions to be processed by the encryption engine;
- (c) random access memory;
- 10 (d) means for placing decrypted output from the encryption engine into the random access memory.

2. A method for increasing the security and efficiency of cryptographic processing resources for
15 postal franking machines, comprising:

- (a) obtaining encrypted code in portions to be processed by an encryption engine;
- (b) placing decrypted output from the encryption engine into random access memory.

20 3. A system for protecting cryptographic processing and memory resources for postal franking machines, comprising:

- (a) (1) zeroizing circuitry, (2) read only memory, (3) random access memory, (4) a
25 clock circuit, (5) non-volatile memory, (6) central cryptographic processor, (7) logic for addressing and data flow, (8)

crypto key retention, (9) signature
algorithm execution, (10) random number
generator, (11) interrupt control and
porting, (12) real time calendar
clocking and watch-dog timer, (13) hash
algorithm, (14) secure memory management
unit, and (15) host interface, all
disposed within a PCMCIA Card;

5

10

(b) means disposed within the PCMCIA Card
for monitoring the amount of time a host
controller is taking to complete a bus
transaction;

15

(c) means disposed within the PCMCIA Card
for comparing the monitored amount of
time to a predetermined reference time;

20

(d) means disposed within the PCMCIA Card
for refusing to permit completion of the
bus transaction if the monitored amount
of time exceeds the predetermined
reference time;

25

(e) an encryption engine disposed within
the PCMCIA Card;

(f) means for obtaining encrypted code in
portions to be processed by the
encryption engine;

30

(g) random access memory disposed within
the PCMCIA Card;

(h) means for placing decrypted output
from the encryption engine into the
random access memory.

4. A system for protecting cryptographic processing and memory resources for postal franking machines, comprising:

- 5 (a) (1) zeroizing circuitry, (2) read only memory, (3) random access memory, (4) a clock circuit, (5) non-volatile memory, (6) central cryptographic processor, (7) logic for addressing and data flow, (8) crypto key retention, (9) signature
10 algorithm execution, (10) random number generator, (11) interrupt control and porting, (12) real time calendar clocking and watch-dog timer, (13) hash algorithm, (14) secure memory management
15 unit, and (15) host interface, all disposed within a PCMCIA Card;
- (b) means disposed within the PCMCIA Card for monitoring the amount of time a host controller is taking to complete a bus
20 transaction;
- (c) means disposed within the PCMCIA Card for comparing the monitored amount of time to a predetermined reference time;
- 25 (d) means disposed within the PCMCIA Card for refusing to permit completion of the bus transaction if the monitored amount of time exceeds the predetermined reference time.

5. A system for protecting cryptographic
30 processing and memory resources for postal franking machines, comprising an Application Specific Integrated

15

Circuit having (1) zeroizing circuitry, (2) read only memory, (3) random access memory, (4) a clock circuit, (5) non-volatile memory, (6) central cryptographic processor, (7) logic for addressing and data flow, (8) 5 crypto key retention, (9) signature algorithm execution, (10) random number generator, (11) interrupt control and porting, (12) real time calendar clocking and watch-dog timer, (13) hash algorithm, (14) secure memory management unit, and (15) host interface.

10 6. A system for protecting cryptographic processing and memory resources for postal franking machines, comprising:

(a) an Application Specific Integrated
Circuit having (1) zeroizing circuitry,
15 (2) read only memory, (3) random access memory, (4) a clock circuit, (5) non-volatile memory, (6) central cryptographic processor, (7) logic for addressing and data flow, (8) crypto key retention, (9)
20 signature algorithm execution, (10) random number generator, (11) interrupt control and porting, (12) real time calendar clocking and watch-dog timer, (13) hash algorithm, (14) secure memory management
25 unit, and (15) host interface;

(b) said Application Specific Integrated Circuit being disposed within a Personal Computer Memory International Association card.

30 7. A method for protecting cryptographic processing and memory resources for postal franking machines, comprising locating the resources to be

protected within an Application Specific Integrated Circuit.

8. A system for protecting cryptographic processing and memory resources for postal franking machines, comprising (1) zeroizing circuitry, (2) read only memory, (3) random access memory, (4) a clock circuit, (5) non-volatile memory, (6) central cryptographic processor, (7) logic for addressing and data flow, (8) crypto key retention, (9) signature algorithm execution, (10) random number generator, (11) interrupt control and porting, (12) real time calendar clocking and watch-dog timer, (13) hash algorithm, (14) secure memory management unit, and (15) host interface, all disposed within a PCMCIA Card.


9. A method for protecting cryptographic processing and memory resources for postal franking machines, comprising locating the resources to be protected within a PCMCIA Card.

10. A method for protecting cryptographic processing and memory resources for postal franking machines disposed within PCMCIA Card, comprising:

- (a) monitoring the amount of time a host controller is taking to complete a bus transaction;
- (b) comparing the monitored amount of time to a predetermined reference time;
- (c) refusing to permit completion of the bus transaction if the monitored amount of time exceeds the predetermined reference time.

11. A system for protecting cryptographic processing and memory resources for postal franking machines, comprising:

- 5 (a) an Application Specific Integrated Circuit having (1) zeroizing circuitry, (2) read only memory, (3) random access memory, (4) a clock circuit, (5) non-volatile memory, (6) central cryptographic processor, (7) logic for addressing and data flow, (8) crypto key retention, (9) signature algorithm execution,
10 (10) random number generator, (11) interrupt control and porting, (12) real time calendar clocking and watch-dog timer, (13) hash algorithm, (14) secure memory management
15 unit, and (15) host interface;
- (b) an encryption engine disposed within the PCMCIA Card;
- (c) means for obtaining encrypted code in portions to be processed by the encryption
20 engine;
- (d) random access memory disposed within the PCMCIA Card;
- (e) means for placing decrypted output from the encryption engine into the random access
25 memory.



2/3




FIG. 2

3/3





FIG. 3



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 9/00		A3	(11) International Publication Number: WO 98/20461
			(43) International Publication Date: 14 May 1998 (14.05.98)
(21) International Application Number: PCT/US97/15856 (22) International Filing Date: 7 November 1997 (07.11.97) (30) Priority Data: 60/030,537 7 November 1996 (07.11.96) US 60/050,043 18 June 1997 (18.06.97) US 60/054,105 29 July 1997 (29.07.97) US (71) Applicant (for all designated States except US): ASCOM HASLER MAILING SYSTEMS, INC. [US/US]; 19 Forest Parkway, Shelton, CT 06484 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): SCHWARTZ, Robert [US/US]; 191 Linden Avenue, Branford, CT 06405 (US). BROOKNER, George [US/US]; 11 Surrey Drive, Norwalk, CT 06851 (US). NACLERIO, Edward [US/US]; 49 Scenic Road, Madison, CT 06443-1738 (US). (74) Agent: FERENCO, Stanley, D., III; Oppedahl & Larson, Suite 309, 1992 Commerce Street, Yorktown Heights, NY 10598-4412 (US).			(81) Designated States: CA, JP, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> (88) Date of publication of the international search report: 8 October 1998 (08.10.98)

(54) Title: SYSTEM FOR PROTECTING CRYPTOGRAPHIC PROCESSING AND MEMORY RESOURCES FOR POSTAL FRANKING MACHINES



(57) Abstract

An improved system for protecting cryptographic processing and memory for postal franking machines. Appropriate cryptographic processing and memory resources are contained in a Postal Security Device (PSD) (5), which defines a cryptographic and physical boundary. Cryptographic processing (18) occurs in the PSD, which provides security to these resources, thereby minimizing a successful fraudulent attack on the system. Speed of the cryptographic processing is also increased. The PSD may be in the form of an Applications Specific Integrated Circuit (ASIC) or Personal Computer Memory Card International Association (PCMCIA) Card.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US97/15856

A. CLASSIFICATION OF SUBJECT MATTER IPC(6) :H04L 9/00 US CL :380/51, 23, 50 According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) U.S. : 380/51, 23, 50, 55, 21 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4,934,846 A (GILHAM) 19 June 1990	1-11
A, P	US 5,602,921 A (RAMADEI) 11 February, 1997	1-11
A, P	US 5,682,427 A (SEESTROM) 28 October 1997	1-11
A	US 5,448,641 A (PINTSOV, et al.) 05 September 1995	1-11
A	US 5,535,279 A (SEESTROM) 09 July 1996	1-11
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* *A* *E* *L* *O* *P*	Special categories of cited documents: document defining the general state of the art which is not considered to be of particular relevance earlier document published on or after the international filing date document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) document referring to an oral disclosure, use, exhibition or other means document published prior to the international filing date but later than the priority date claimed	*T* *X* *Y* *A* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art document member of the same patent family
Date of the actual completion of the international search 22 APRIL 1998		Date of mailing of the international search report 14 MAY 1998
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230		Authorized officer <i>David C. Goodenough</i> DAVID CAIN Telephone No. (703) 305-1836

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.